

SPECIFICATIONS

Waterhog™ Modular Interlocking Carpet Tile Square

Product Number Square Pattern: 2210

Surface

Fiber Type:	Needle-punched Solution-dyed polypropylene
Weight:	24 ozs./sy.
Nub Height:	7/16"
Design:	Square

Backing

Type:	100% SBR Rubber
Thickness:	.190" – Nubs .050" – Between Nubs
Durometer:	75
Tensil:	1200 PSI

Testing

- ASTM C 1028-89 Static Coefficient of Friction. Dry . 70
- Passes Flammability Standard DOC-FF-1-70
- Anti-Static
- Dimensional Stability AACHENER test: less than 0.2% change.

A
CWF Flooring, Inc.
Company

SPECIFICATIONS

- Exclusive rubber reinforced face nubs prevent pile from crushing in high traffic areas, thereby maintaining high performance and extending product life.
- Should not be in areas exposed to animal fats (kitchens) or petroleum products.
- Not adversely affected by salt or ice melt.
- Easy to clean: Just vacuum. An upright carpet extractor may also be used with permanent adhesives.
- Size: Modular Tiles-18"x18" or 36"x36"
Borders-18" side, 18" corners or 36" sides, 36" corners
- Certified slip-resistant by the National Floor Safety Institute.
- Recommended in high traffic areas such as entrances, recessed mat wells, lobbies, vestibules and elevators.

www.PeelandStickCarpetTiles.com

