



SPECIFICATIONS

Waterhog™ Classic Tile

Product Number 210 Square Pattern

Product Number 219 Diagonal Pattern

Product Number 216 Diamond Pattern

Product Number 220 Geometric Pattern

Surface

Fiber Type:	Needle-punched Solution-dyed polypropylene
Weight:	24 ozs./sy.
Nub Height:	1/4" & 7/16"
Design:	Square, Diamond, Diagonal, Geometric

Backing

Type:	100% SBR Rubber
Thickness:	.190" – Nubs .050" – Between Nubs
Durometer:	75
Tensil:	1200 PSI

A
CWF Flooring, Inc.
Company

Testing

- ASTM C 1028-89 Static Coefficient of Friction. Dry . 70
- Passes Flammability Standard DOC-FF-1-70
- Anti-Static
- Dimensional Stability AACHENER test: less than 0.2% change.
- Install with solvent-free permanent adhesive.
- Exclusive rubber reinforced face nubs prevent pile from crushing in high traffic areas, thereby maintaining high performance and extending product life.
- Should not be in areas exposed to animal fats (kitchens) or petroleum products.
- Not adversely affected by salt or ice melt.
- Easy to clean: Just vacuum. An upright carpet extractor may also be used with permanent adhesives.
- Size: 18" x 18"
- Certified slip-resistant by the National Floor Safety Institute.
- Recommended in high traffic areas such as entrances, recessed mat wells, lobbies, vestibules and elevators.